PATENT

TAN

IN THE UNITED STATES PATENT OFFICE

Application of

GEPFREY, Dale A., et al

Serial No. Filed 10/762,415 01/22/2004

Title

WATER-TIGHT WINDOWS WITH PREFORMED CORNERS

Art Unit

3634

Examiner Docket No.

SIMBU, Gregory L. GII 001 PCT-US Nat'l

Mail Stop Patent Amendment Commissioner for Patents P.O. Box 1450 ALEXANDRIA VA 22313-1450

Sir:

Amendments

In the specification, please cancel the Abstract presently on file, and enter the following Abstract:

Abstract

A window construction comprising an outer window framework having lineal sections providing a header (20H), a sill (30S), and a pair of jambs (23L, 23R), joined by formed integral corner sections (10) having joint ends which extend from the corner sections at a predetermined angle with respect to each other. The corner sections and lineal sections have complementary cross-sectional configurations, and are formed of essentially the same material so they may be welded together (Fig. 6). In another configuration these ends may have integral splines (12) as part of the complementary cross-sectional configurations (Figs. 3, 4 & 5) and are mechanically joined. In either configuration, the joints between the corner section and the lineal sections achieve rigid water-tight corner joints and provide a water-tight window. The outer framework incorporates flanges (25) for mounting the complete window in a window aperture of a building or vehicle and channels (27) for receiving an inner framework of sashes and/or vents, and providing a peripheral seal for the same. The inner framework includes a header (40H), a sill (40S), and jambs (43L, 43R). The header, sill and jambs of both the outer and inner frames are lineal extrusions having cross-sectional configurations that are compatible with the profiles of the corner pieces.